

Cone Crushers

HYDRAULIC (MODEL -H)

Includes a fully hydraulic tramp relief, clearance, and adjustment.



SEMI HYDRAULIC (MODEL -S)

Includes a spring relief, hydraulic clearance, and hydraulic adjustment.



HYDRAULIC CLEARING

HYDRAULIC ADJUSTMENT

HEAVY DUTY DESIGN

COST EFFECTIVE & LONG LIFE

HIGH PRODUCTIVITY

ADVANTAGES

- Available in up to 500HP (370KW) units
- Large eccentric with high rotation speed
- Exclusive self-tightening mantle and concave
- Hardened and tempered chrome molybdenum eccentric shaft
- Feed plate designed for even material distribution
- Supplied complete with hydraulic system
- Automatic hydraulic chamber adjustment
- Option for automatic hydraulic or spring discharge clearing device for easy tramp iron release
- Automated lubrication system
- Heavy duty V-belt drive on adjustable motor base
- Standard replacement parts

SIZING CHART

Throughput (TPH)

Closed side Setting

Model	6mm	8mm	10mm	13mm	16mm	19mm	22mm	25mm	32mm	38mm	45mm	51mm
CC100-HP	42-52	47-57	52-66	57-76	66-85	71-90	76-95	80-104	95-133			
CC200-HP			86-116	116-146	136-178	146-188	156-196	166-216	186-231	206-246		
CC300-HP			110-136	146-180	176-216	196-236	216-256	226-276	246-316	296-376	346-436	
CC400-HP			136-171	180-226	221-276	250-316	270-340	290-366	320-426	356-486	406-558	460-626

APPLICATIONS

- Mining
- Aggregate
- Demolition
- Industrial
- Construction
- Environmental

Contact Westpro and find your process solution today.

